



HHW


UNIQUE AND UNPRECEDENTED

The HHW luminaire, with its conical light cover measuring almost one metre in height, is an iconic visual element in public spaces. The HHW can be supplied with different light distributions so there is always enough light where and when required. The luminaire is also future-proof. The HHW incorporates UniCliq; a unique system that allows the most up-to-date LED lighting solutions to be implemented easily and quickly in the existing luminaire.

Application areas



DIMENSIONS HHW in mm



Characteristics



PRODUCT SPECIFICATIONS

- Polycarbonate top cover, batch-dyed black (RAL9005) or grey (RAL7032)
- Light cover polycarbonate, ice-structured finish
- UniCliq-unit
- Pole-mounted size: 60 mm
- Mass: ± 8 kg (depends on model)
- Wind surface: ± 0.2 m²
- Safety class I
- Assembly-, installation- and maintenance-friendly
- Voltage: 230 / 240 V, 50 Hz
- CRI: > 70
- Colour temperature neutral white (4000K) or warm white (3000K)
- Expected lifespan 100.000 hours at T environment = 25°C (L96/F10)
- Different lens configurations

OPTIONS

- Other RAL colour
- Dimmable
- Dali
- Safety class: II
- Constant Lumen Output (CLO)

UNICLIQ LED UNIT

The HHW can be easily equipped with the latest lighting technology thanks to the UniCliq unit.



Lightronics supplies its luminaires as standard as Easy Light, with five standard dimming schedules (1A, 2A, 3A, 4A or 5A) that can switch capacity and brightness based on pre-set times.

HHW | LED²WELL CORE OUR STANDARD LIGHTING SOLUTION

		3000K		4000K	
Number of LEDs	Lumen	LED-power (W)	System power (W)	LED-power (W)	System power (W)
16	800	5,7	8,0	5,5	7,7
	1050	6,8	9,0	6,3	8,6
	1200	7,5	9,8	7,2	9,5
	1350	8,1	10,5	7,9	10,2
	1500	8,8	11,2	8,5	10,9
	1600	9,3	11,7	9,0	11,4
	1800	10,4	12,8	10,0	12,4
	2000	11,2	13,7	10,6	13,1
	2150	12,4	14,9	11,5	13,9
	2300	13,5	16,1	12,6	15,1
	2500	14,8	17,5	14,2	16,8
	2750	16,6	19,4	15,7	18,5
	3000	18,5	21,4	17,3	20,1