



PGA

ENERGY-EFFICIENT LIGHTINGFOR PARKING GARAGES

The PGA LED luminaire ensures that visitors can easily find their way in your parking garage. This energy-efficient surface-mount luminaire always provides optimum lighting where needed, giving users a safe and secure feeling. The PGA uniformly projects light into the farthest corners. In addition, the luminaire is dust-tight and waterproof, so you are guaranteed good lighting in your parking garage for many years. In addition to use as parking garage lighting, the PGA luminaire is also ideal for industrial buildings and technical rooms.



Applications







Features









OPTION







PRODUCT SPECIFICATIONS


- Housing made of impactproof, flame-retardant, UVstabilised polycarbonate
- · Standard colour RAL 7032
- · Light cover made of UV-stabilised polycarbonate, frosted
- Dimensions (d x h): 101mm x 101mm
- · Cable entry on the side
- · Stainless steel fastening clips
- Voltage: 230/240 V, 50 Hz
- · Assembly-, installation- and maintenance friendly
- · CRI > 80
- Colour temperature warm white (3000K) or neutral white (4000K)
- Expected lifespan 100.000 hours at T-ambient = 25°C (L80/F10)

OPTIONS

- Emergency/continious lighting, incl. ATF (1 hour)
 from casing length 1277mm
- Extern dimmable (Dali) or 1-10V
- SmartScan
- · Asymmetrical light distribution
- · Mounting brackets
- · Connectors for quick installation

DIMENSIONS PGA







Luminaires in the Easy Light version have a fixed luminous flux.



The smart lighting system SmartScan optimises the use of luminaires in your environment. Thanks to wireless communication, there is always sufficient light when required and energy is saved.



PGA | EASY LIGHT

| Lumen | Size L (mm) | Size A (mm) | LED power (W) | System power (W) |
|-------|------------------|-------------|---------------|------------------|
| 1300 | 660 (Housing 2) | 390 | 6,9 | 8,9 |
| 2200 | 660 (Housing 2) | 390 | 12,1 | 14,5 |
| 3600 | 1277 (Housing 4) | 800 | 19,5 | 22,4 |
| 4400 | 1277 (Housing 4) | 800 | 24,2 | 27,5 |
| 5000 | 1277 (Housing 4) | 800 | 28,5 | 31,7 |
| 6000 | 1277 (Housing 4) | 800 | 34,5 | 38,3 |
| 6500 | 1277 (Housing 4) | 800 | 38,0 | 41,7 |
| 7000 | 1277 (Housing 4) | 800 | 40,6 | 44,5 |
| 8000 | 1277 (Housing 4) | 800 | 46,8 | 51,2 |
| 8800 | 1573 (Housing 5) | 800 | 47,8 | 51,9 |

POLAR DIAGRAM PGA

